

Department of Energy

§ 851.23

identifying such hazards. The Head of DOE Field Element, with concurrence by the Cognizant Secretarial Officer, has 90 days to accept the closure facility hazard controls or direct additional actions to either:

- (1) Achieve technical compliance; or
- (2) Provide additional controls to protect the workers.

(c) Contractors must perform the activities identified in paragraph (a) of this section, initially to obtain baseline information and as often thereafter as necessary to ensure compliance with the requirements in this Subpart.

§ 851.22 Hazard prevention and abatement.

(a) Contractors must establish and implement a hazard prevention and abatement process to ensure that all identified and potential hazards are prevented or abated in a timely manner.

(1) For hazards identified either in the facility design or during the development of procedures, controls must be incorporated in the appropriate facility design or procedure.

(2) For existing hazards identified in the workplace, contractors must:

- (i) Prioritize and implement abatement actions according to the risk to workers;
- (ii) Implement interim protective measures pending final abatement; and
- (iii) Protect workers from dangerous safety and health conditions;

(b) Contractors must select hazard controls based on the following hierarchy:

- (1) Elimination or substitution of the hazards where feasible and appropriate;
- (2) Engineering controls where feasible and appropriate;
- (3) Work practices and administrative controls that limit worker exposures; and
- (4) Personal protective equipment.

(c) Contractors must address hazards when selecting or purchasing equipment, products, and services.

§ 851.23 Safety and health standards.

(a) Contractors must comply with the following safety and health standards that are applicable to the hazards at their covered workplace:

(1) Title 10 Code of Federal Regulations (CFR) 850, "Chronic Beryllium Disease Prevention Program."

(2) Title 29 CFR, Parts 1904.4 through 1904.11, 1904.29 through 1904.33; 1904.44, and 1904.46, "Recording and Reporting Occupational Injuries and Illnesses."

(3) Title 29 CFR, Part 1910, "Occupational Safety and Health Standards," excluding 29 CFR 1910.1096, "Ionizing Radiation."

(4) Title 29 CFR, Part 1915, "Shipyard Employment."

(5) Title 29 CFR, Part 1917, "Marine Terminals."

(6) Title 29 CFR, Part 1918, "Safety and Health Regulations for Longshoring."

(7) Title 29 CFR, Part 1926, "Safety and Health Regulations for Construction."

(8) Title 29 CFR, Part 1928, "Occupational Safety and Health Standards for Agriculture."

(9) American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices," (2005) (incorporated by reference, see § 851.27) when the ACGIH Threshold Limit Values (TLVs) are lower (more protective) than permissible exposure limits in 29 CFR 1910. When the ACGIH TLVs are used as exposure limits, contractors must nonetheless comply with the other provisions of any applicable expanded health standard found in 29 CFR 1910.

(10) American National Standards Institute (ANSI) Z88.2, "American National Standard for Respiratory Protection," (1992) (incorporated by reference, see § 851.27).

(11) ANSI Z136.1, "Safe Use of Lasers," (2000) (incorporated by reference, see § 851.27).

(12) ANSI Z49.1, "Safety in Welding, Cutting and Allied Processes," sections 4.3 and E4.3 (1999) (incorporated by reference, see § 851.27).

(13) National Fire Protection Association (NFPA) 70, "National Electrical Code," (2005) (incorporated by reference, see § 851.27).

(14) NFPA 70E, "Standard for Electrical Safety in the Workplace," (2004) (incorporated by reference, see § 851.27).